جي جي سي

GGC

شركة الخليج لفتحات التكييف المركزي


# GULF GRILLES CO.



**SECURITY GRILLES** 

# S-BGU-U SUPPLY SECURITY LINEAR BAR GRILLES 7FRO DEGREE FIXED BLADES AND VOLUME CONTROL DAMPER





### PRODUCT DESCRIPTION:

- The frame and blades are extruded aluminum alloy and are polyester powder coated with a white finish
- The frame has a Typical wall thickness of 1/16"
- The blades are spaced ½" on center and are ¼" thickness at the face
- Mullion bars across the blades provides additional strength
- An opposed blade damper attached and operator is easily adjustable through the face with a screw driver

- The damper frame is separated from the blades with PVC bushings eliminating corrosion and vibration
- Standard finish is white color painted under electrostatic polyester powder coated system. Other colors are available on request
- The fram of whole assembly is welded with G.I sheet 1.2 mm thick casing
- This security is suitable for wall mounting where the high grade of security is needed
- Color-9016


### LISTED WIDTHS

inches	2	2-1/2	3	3-1/2	4	5	6	8	10
mm	50.8	63.5	76.2	88.9	101.6	127	152.4	203.2	254



# R-BGO-X RETURN SECURITY LINEAR BAR GRILLES ZERO DEGREE FIXED BLADES AND VOLUME CONTROL DAMPER







### PRODUCT DESCRIPTION:

- The frame and blades are extruded aluminum alloy and are polyester powder coated with a white finish
- The frame has a Typical wall thickness of 1/16"
- The blades are spaced 1/2" on center and are 1/4" thickness at the face
- Mullion bars across the blades provides additional strength
- An opposed blade damper attached and operator is easily adjustable through the face with a screw driver

- The damper frame is separated from the blades with PVC bushings eliminating corrosion and vibration
- Standard finish is white color painted under electrostatic polyester powder coated system. Other colors are available on request
- The fram of whole assembly is welded with G.I sheet 1.2 mm thick casing
- This security is suitable for wall mounting where the high grade of security is needed
- Color-9016


### LISTED WIDTHS

inches	2	2-1/2	3	3-1/2	4	5	6	8	10
mm	50.8	63.5	76.2	88.9	101.6	127	152.4	203.2	254

### **SECURITY LINEAR BAR GRILLE**



## **INSTALLATION DETAILS**



# SECURITY GRILLES PERFORMANCE DATA

I	300 400 500	009	800	1000	1200
Total Pressure(in.wg)	0.041 0.068 0.109	0.15	0.274	0.424	0.616
CFM	55 70 90	110	145	180	215
NC	- 15	20	29	35	41
Throw(ft)	9 10 14	19	22	24	27
CFM 8	80 105 130	155	210	260	310
NC .	- 11 16	21	30	36	42
Throw(ft) 16	3 19 20	25	29	33	35
CFM 155	5 210 260	310	415	520	625
NC -	15 22	28	33	39	45
Throw(ft) 23	3 26 28	33	39	42	46
CFM 245	5 325 405	485	029	810	970
NC 11	18 24	29	38	42	46
Throw(ft) 28	31 34	40	47	52	22
CFM 480	0 640 800	096	1280	1600	1920
NC -	17 23	28	37	43	49
Throw(ft) 39	9 43 48	48	9	20	78